



PN 40

ČSN 131233 DIN 2635

Přivařovací příruby s krkem

DN	d ₁		D	d	b	k	h ₁	d ₃	s	r	h ₂	d ₄	f	Šroubové otvory		Hm. kg
	DIN 2635	ČSN 131233												počet	d ₂	
15	21,3		95	-	16	65	38	32	2	4	6	45	2	4	14	0,75
		22		17				32	2,5		-					
20	26,9		105	-	18	75	40	40	2,3	4	6	58	2	4	14	1,06
		28		23				41	2,5		-					
25	33,7		115	-	18	85	40	46	2,6	4	6	68	2	4	14	1,29
		32		27				44	2,5		-					
32	42,4		140	-	18	100	42	56	2,6	6	6	78	2	4	18	1,88
		38		33				52	2,5		-					
40	48,3		150	-	18	110	45	64	2,6	6	7	88	3	4	18	2,33
		44,5		39,5				60	2,5		-					
50	60,3		165	-	20	125	48	75	2,9	6	8	102	3	4	18	2,82
		57		51				72	3		-					
65	76,1		185	-	22	145	52	90	2,9	6	10	122	3	8	18	3,74
		76		70							-					
80	88,9		200	-	24	160	58	105	3,2	8	-	138	3	8	18	4,75
		89		82							12					
100	114,3		235	-	24	190	65	134	3,6	8	12	162	3	8	22	6,52
		108		100				128	4		-					
125	139,7		270	-	26	220	68	162		8	12	188	3	8	26	9,07
		133		125				155	4		-					
150	168,3		300	-	28	250	75	192		10	12	218	3	8	26	11,8
		159		150				182	4,5		-					
200	219,1		375	-	34	320	88	244	6,3	10	16	285	3	12	30	21,5
		219		207				243	6		-					
250	273		450	-	38	385	105	306	7,1	12	18	345	3	12	33	34,9
		273		260				300	6,5		-					
300	323,9		515	-	42	450	115	362	8	12	18	410	4	16	33	49,7
		324		309				356	7,5		-					
350	355,6		580	-	46	510	125	408	8,8	12	20	465	4	16	36	68,1
		377		359				415	9		-					
400	406,4		660	-	50	585	135	462	11	12	20	535	4	16	39	96,5
		426		402				466	12		-					
500	508		755	-	52	670	140	562	14,2	12	20	615	4	20	42	117
		530		502				572	14		-					
600			890	-	60	795	150	675	16	18	20	730	5	20	48	142
		630		598							-					